spectrum®

Preparation Date: 09/12/2016



Revision Number: Not Applicable

SAFETY DATA SHEET

Revision Date: Not Applicable

	1. IDENTIFICATION
Product identifier	
Product code:	E1489
Product Name:	Ethyl Glyoxylate Polymer form, (47 Percent in Toluene)
Other means of identification	
Synonyms:	No information available
CAS #:	924-44-7
RTECS #	Not available
CI#:	Not available
Recommended use of the chem	ical and restrictions on use
Recommended use:	For manufacturing or laboratory use only.
Uses advised against	Not for food or drug use.
Supplier:	Spectrum Chemical Mfg. Corp
	14422 South San Pedro St.
	Gardena, CA 90248
	(310) 516-8000.
Order Online At:	https://www.spectrumchemical.com
Emergency telephone number	Chemtrec 1-800-424-9300
Contact Person:	Martin LaBenz (West Coast)
Contact Person:	Ibad Tirmiz (East Coast)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Considered a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Danger

Hazard statements Harmful if swallowed

Causes skin irritation

Causes eye irritation Suspected of damaging fertility or the unborn child May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Highly flammable liquid and vapor



Hazards not otherwise classified (HNOC) Not Applicable

Other hazards

Toxic to aquatic life with long lasting effects Toxic to aquatic life

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/ .? /equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention In case of fire: Use CO2, dry chemical, or foam to extinguish. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove person to fresh air and keep comfortable for breathing. Rinse mouth IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Toluene	108-88-3	53

ETHYL GLYOXYLATE	924-44-7	47
------------------	----------	----

4. FIRST AID MEASURES

First aid measures

General Advice:	National Capital Poison Center in the United States can provide assistance if you have a poison emergency and need to talk to a poison specialist. Call 1-800-222-1222.
Skin Contact:	Wash off immediately with soap and plenty of water removing all contaminated clothing and shoes. Get medical attention. If skin irritation persists, call a physician.
Eye Contact:	Flush eyes with water for 15 minutes. Get medical attention.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Ingestion:	Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effe	cts, both acute and delayed
Symptoms	Causes skin irritation. Causes serious eye irritation. Vapors irritating to eyes and respiratory

 mptoms
 Causes skin irritation. Causes serious eye irritation. Vapors irritating to eyes and respiratory

 tract. Drowsiness. Dizziness. May cause headache. Coughing and wheezing. May cause

 pulmonary edema. Ingestion may cause nausea, vomiting, and diarrhea. Aspiration hazard

 if swallowed - can enter the lungs and cause damage. Aspiration into the lungs may cause

 chemical pneumonitis.

Indication of any immediate medical attention and special treatment needed

Notes to Physician:

Treat symptomatically.

Protection of first-aiders

First-Aid Providers: Avoid exposure to blood or body fluids. Wear gloves and other necessary protective clothing. Dispose of contaminated clothing and equipment as bio-hazardous waste.

5. FIRE-FIGHTING MEASURES

Extinguishing Media Suitable Extinguishing Media:	Dry chemical. Carbon dioxide (CO2). Water spray mist or foam.
Unsuitable Extinguishing Media:	Do not use a solid (straight) water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	
Hazardous Combustion Products:	Carbon monoxide; Carbon dioxide
Hazardous Combustion Products:	No information available.
Specific hazards:	Flammable May be ignited by heat, sparks or flames Vapor may travel considerable distance to source of ignition and flash back Vapors may form explosive mixtures with air Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers,

basements, tanks) Container explosion may occur under fire conditions or when heated Fire may produce irritating, corrosive and/or toxic gases

Special Protective Actions for Firefighters

Specific Methods:

Special Protective Equipment for Firefighters:

Water mist may be used to cool closed containers. For larger fires, use water spray or fog. Cool containers with flooding quantities of water until well after fire is out.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions:	Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. In case of large spill, water spray or vapor suppressing foam may be used to reduce vapors, but may not prevent ignition in closed spaces.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Prevent entry into waterways, sewers, basements or confined areas.
Methods and material for contai	nment and cleaning up_
Methods for containment	Absorb spill with inert material (e.g. vermiculite, dry sand or earth), then place in a suitable chemical waste container. In case of large spill, dike if needed. Dike far ahead of liquid spill for later disposal.
Methods for cleaning up	Use appropriate tools to put the spilled material in a suitable chemical waste disposal container. Use only non-sparking tools. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Technical Measures/Precautions:

Provide sufficient air exchange and/or exhaust in work rooms. Remove all sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from incompatible materials.

Safe Handling Advice

Wear personal protective equipment. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothing. Take precautionary measures against static discharges. Keep away from heat and sources of ignition. Do not breathe vapors or spray mist. Do not ingest. When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Technical Measures/Storage Conditions:

Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original

container. Keep away from heat and sources of ignition. Store in a segregated and approved area. Store away from incompatible materials. Air sensitive. Store under inert gas. Packed under Argon.

Incompatible Materials:

Oxidizing agents Acids Silver perchlorate Sodium dilfuoride Tetranitromethane Uranium hexafluoride Bromine trifluoride Nitrogen oxides Halogens

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

National occupational exposure limits

United States

Components	CAS-No.	OSHA	NIOSH	ACGIH	AIHA WHEEL
Toluene	108-88-3	200 ppm TWA 300 ppm Ceiling	100 ppm TWA 375 mg/m ³ TWA 150 ppm STEL 560 mg/m ³ STEL	20 ppm TWA	None
ETHYL GLYOXYLATE	924-44-7	None	None	None	None

Canada

Components	CAS-No.	Canada - Alberta	Canada - British Columbia	Canada - Ontario	Canada - Quebec
Toluene	108-88-3	50 ppm TWA 188 mg/m³ TWA	20 ppm TWA	20 ppm TWA	50 ppm TWAEV 188 mg/m ³ TWAEV
ETHYL GLYOXYLATE	924-44-7	None	None	None	None

Australia and Mexico

Components	CAS-No.	Australia	Mexico
Toluene	108-88-3	574 mg/m ³ STEL	50 ppm TWA
		150 ppm STEL	188 mg/m³ TWA
		50 ppm TWA	
		191 mg/m ³ TWA	
ETHYL GLYOXYLATE	924-44-7	None	None

Appropriate engineering controls

Engineering measures to reduce exposure:

Ensure adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors and mist below their respective threshold limit value.

Individual protection measures, such as personal protective equipment

Personal Protective Equipment

Eye protection:	Goggles
Skin and body protection:	Chemical resistant apron. Long sleeved clothing. Gloves.
Product code: E1489	Product name: Ethyl Glyoxylate Polymer form, (47 Percent in Toluene)

Respiratory protection:

Hygiene measures:

Vapor respirator. Be sure to use an approved/certified respirator or equivalent.

Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Odor: No information available.

Molecular/Formula weight: No information available

Flash Point Tested according to: Not available

Upper Explosion Limit (%): No information available

Boiling point/range(°C/°F): 110°C (230°F)

Specific gravity: No information available

Evaporation rate: No information available

Odor threshold (ppm): No information available

Miscibility:

For Toluene: Miscible with alcohol Miscible with Chloroform Miscible with Acetone Miscible with Ether Miscible with glacial Acetic Acid Miscible with Carbon disulfide Appearance: Clear.

Taste No information available.

Flammability: No information available

Autoignition Temperature (°C/°F): No information available

Melting point/range(°C/°F): No information available

Bulk density: No information available

pH: No information available

Vapor density: No information available

Partition coefficient (n-octanol/water): No information available

Solubility:

For Toluene: Practically insoluble in water Soluble in Ethanol Soluble in Ether Soluble in Benzene Soluble in Chloroform Soluble in Acetone Soluble in Carbon Disulfide Soluble in glacial Acetic acid **Color:** Pale Yellow. Pale Yellow Red.

Formula: No information available

Flashpoint (°C/°F): 7°C (45°F)

Lower Explosion Limit (%): No information available

Decomposition temperature(°C/°F): No information available

Density (g/cm3): 1.03

Vapor pressure @ 20°C (kPa): No information available

VOC content (g/L): No information available

Viscosity: No information available

10. STABILITY AND REACTIVITY

Reactivity

Reacts vigorously with oxidizing agents

Reactive with strong oxidizers, silver perchlorate, sodium difluoride, tetranitromethane, Uranium Hexafluoride Ignition occurs when potassium tert-butoxide reacts with n-propanol

Toluene forms an explosive mixture with Tetranitromethane.

Reacts photochemically with nitrogen oxides or halogens to form nitrotoluene, nitrobenzene, and nitrophenol and halogenated products, respectively.

Chemical stability

Stability:

Product code: E1489

Stable under recommended storage conditions.

Product name: Ethyl Glyoxylate Polymer form, (47 Percent in Toluene) Possibility of Hazardous Reactions: Hazardous polymerization does not occur

Conditions to avoid:	Heat. Ignition sources. Incompatible materials. Exposure to air.
Incompatible Materials:	Oxidizing agents Acids Silver perchlorate Sodium dilfuoride Tetranitromethane Uranium hexafluoride Bromine trifluoride Nitrogen oxides Halogens
Hazardous decomposition products:	Carbon monoxide. Carbon dioxide.
Other Information Corrosivity:	No information available

Special Remarks on Corrosivity: No information available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principal Routes of Exposure:

Ingestion. Skin. Eyes. Inhalation.

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document Component Information

Toluene
CAS-No. 108-88-3
LD50/oral/rat = 636 mg/kg Oral LD50 Rat
LD50/oral/mouse = No information available
LD50/dermal/rabbit = 8390 mg/kg Dermal LD50Rabbit
26.4 mg/kg (RTECS)
LD50/dermal/rat = 12124 mg/kg Dermal LD50 Rat
LC50/inhalation/rat = 12.5 mg/L Inhalation LC50 Rat 4 h
26700 ppm Inhalation LC50 Rat 1 h
LC50/inhalation/mouse = 30000 mg/m ³ 2 h (RTECS)
19900 mg/m ³ 7 h (RTECS)
Other LD50 or LC50information = No information available
ETHYL GLYOXYLATE
CAS-No. 924-44-7
LD50/oral/rat = No information available
LD50/oral/mouse = No information available
LD50/dermal/rabbit = No information available
LD50/dermal/rat = No information available
LC50/inhalation/rat = No information available
LC50/inhalation/mouse = No infomation available
Other LD50 or LC50information = No information available

Product Information

LD50/oral/rat = VALUE- Acute Tox Oral = 636 mg/kg

LD50/oral/mouse = Value - Acute Tox Oral = No information available

LD50/dermal/rabbit VALUE-Acute Tox Dermal = 8390 mg/kg

LD50/dermal/rat VALUE -Acute Tox Dermal = 12124 mg/kg

LC50/inhalation/rat VALUE-Vapor = 12.5 mg/l VALUE-Gas = No information available VALUE-Dust/Mist = No information available

LC50/Inhalation/mouse VALUE-Vapor = 19900 mg/m³ VALUE - Gas = No information available VALUE - Dust/Mist = No information available

Symptoms

Skin Contact:	Causes skin irritation. Mild skin irritation. Moderate skin irritation.	
Eye Contact:	Causes serious eye irritation. Causes conjunctivitis. Causes lacrimation. Cause blepharospasm, corneal edema, corneal abrasions. Irritating, but will not permanently injure eye tissue. Exposure to high concentration of vapor may ca pupillary dilation or pupillary constriction, and impaired pupillary reaction.	es use
Inhalation	Irritating to respiratory system. May cause nausea, vomiting. May cause bronchospasms. May cause bronchitis. May cause chemical pneumonitis. It ma cause pulmonary edema. Inhalation of high concentrations of vapors may cause dizziness or suffocation. Inhalation of high concentrations of vapor may cause anesthetic effects. It may affect behavior/central nervous system (excitation an wakefulness followed by central nervous system depression - headache, irritability, nervousness, insomnia, ataxia, seizures, tremors, hallucinations, euphoria, memory, loss, somnolence, fatigue, sedation, general anesthetic. Ma affect cardiovascular system (bradycardia, tachycardia, cardiac arrhythmias). N affect the brain. It may affect the cardiovascular system (hypotension, cardiac arrhythmias, cardiac arrest). May affect the kidneys. It may affect the blood (changes in white blood cell count, changes in other cell count). It may affect the bone marrow (changes in bone marrow).	ay ;e d ay ∕lay
Ingestion	Harmful if swallowed. Aspiration hazard if swallowed. Aspiration into the lungs cause chemical pneumonitis. Causes digestive (gastrointestinal) tract irritation. Ingestion may cause nausea, vomiting, diarrhea. May cause abdominal pain. M affect the cardiovascular system (hypertension, increase in pulse rate, arrhythmias). It may affect the brain. May affect behavior/central nervous system (muscle contraction or spasticity). May affect behavior/central nervous system (ataxia). May affect behavior/central nervous system (convulsions). May affect respiration (acute pulmonary edema). May affect blood (changes in serum composition).	can ∕lay m
Aspiration hazard	May be fatal if swallowed and enters airways.	
Product code: E1489	Product name:Ethyl Glyoxylate8Polymer form, (47 Percent in Toluene)	/ 14

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: No information available.	Chronic Toxicity	Prolonged or repeated skin contact may cause dermatitis and defatting, dryness, and cracking of the skin. Prolonged or repeated inhalation may cause nausea, vomiting, abdominal pain, loss of appetite, and weight loss. Prolonged or repeated inhalation may affect respiration (respiratory failure). Prolonged or repeated inhalation may cause central nervous system effects. Prolonged or repeated ingestion or inhalation may affect the brain (degenerative changes). Prolonged or repeated inhalation may affect the peripheral nervous system (weakness, peripheral neuropathy with paresthesia - a tingling, pricking, or numbness of the skin (known as the feeling of "pins and needles) generally of the hands and feet (extremities)). Prolonged or repeated inhalation may cause decreased visual acuity, impaired color vision, optic atrophy, blindness, and ototxicity. Prolonged or repeated inhalation may affect the cardiovascular system (dysrhythmias, tachycardia, cardiomyopathy). Prolonged or repeated inhalation may affect the liver. Prolonged or repeated inhalation may affect the blood (pigmented or nucleated red blood cells). Prolonged or repeated inhalation may cause metabolic acidosis, hypokalemia. Prolonged or repeated inhalation may cause rhadbomyolysis, a breakdown of muscle fibers resulting in the release of muscle fiber contents (myoglobin) into the bloodstream. This may be harmful to the kidneys and frequently result in kidney damage. Prolonged or repeated ingestion may affect the blood (changes in serum composition). Prolonged or repeated ingestion may affect the blood (changes or repeated ingestion may affect the blood (changes in serum composition). Prolonged or repeated ingestion may affect the blood (changes in white blood cell count). Prolonged or repeated inhalation may affect the blood (changes in white blood cell count). Prolonged or repeated inhalation may affect the blood (changes in white blood cell count). Prolonged or repeated inhalation may affect the blood (changes in white blood cell count). Prolonged or
	Sensitization:	No information available.

Mutagenic Effects:	For Toluene:
-	May affect genetic material
	Experiments with bacteria and/or yeast have shown mutagenic effects

Carcinogenic effects: Not classifiable as to its carcinogenicity to humans. Not classifiable as a human carcinogen.

Components	CAS-No.	IARC	ACGIH - Carcinogens	NTP	OSHA HCS - Carcinogens	Australia - Notifiable Carcinogenic Substances	Australia - Prohibited Carcinogenic Substances
Toluene	108-88-3	Group 3 - Monograph 71 [1999] Monograph 47 [1989]	A4 Not Classifiable as a Human Carcinogen	Not listed	Not listed	Not listed	Not listed
	924-44-7	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

ACGIH (American Conference of Governmental Industrial Hygienists)

IARC (International Agency for Research on Cancer)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive toxicity	Suspected of damaging fertility or the unborn child		
Reproductive Effects:	For Toluene: May cause adverse developmental effects May cause harm to the unborn child Experiments have shown reproductive toxicity effects on laboratory animals An association between increased risk of spontaneous abortion and occupational exposure to Toluene at least three times a week in early pregnancy was observed in a case-control study of 206 spontaneous abortions among laboratory workers Chronic abuse of toluene during pregnancy can result in miscarriages		
Developmental Effects: Teratogenic Effects:	No information available For Toluene: May cause birth defects (teratogenic effects) Showed teratogenic effects in animal experiments Microcephaly, central nervous system dysfunction, cerebellar dysfunction, growth deficiency, developmental delay, and craniofacial anomalies, similar in some regards to those seen in fetal alcohol syndrome, have been described in children born of women who had abused toluene during their pregnancies		
Specific Target Organ Toxicity			
STOT - single exposure STOT - repeated exposure Target Organs:	STOT - single exposure. central nervous system. May cause damage to organs through prolonged or repeated exposure. Liver. Kidneys. Skin. Brain. Central nervous system. Peripheral nervous system.		

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity effects:	Aquatic environment.	
Toluene - 108-88-3		
Freshwater Algae Data:	12.5 mg/L EC50 Pseudokirchneriella subcapitata 72 h 433 mg/L EC50 Pseudokirchneriella subcapitata 96 h	
Freshwater Fish Species Data:	 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96 h static 1 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96 h static 1 15.22 - 19.05 mg/L LC50 Pimephales promelas 96 h flow-through 1 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96 h flow-through 1 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96 h static 1 12.6 mg/L LC50 Pimephales promelas 96 h static 1 28.2 mg/L LC50 Poecilia reticulata 96 h semi-static 1 5.8 mg/L LC50 Oncorhynchus mykiss 96 h semi-static 1 	
Water Flea Data:	5.46 - 9.83 mg/L ÉC50 Daphnia magna 48 h 11.5 mg/L EC50 Daphnia magna 48 h	
Persistence and degradability:	No information available	
Bioaccumulative potential:	No information available.	
Mobility:	No information available.	

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Waste from residues / unused products:

Waste must be disposed of in accordance with Federal, State and Local regulation.

Contaminated packaging:

Empty containers should be taken for local recycling, recovery or waste disposal

Components	CAS-No.	RCRA - F Series Wastes	RCRA - K Series Wastes	RCRA - P Series Wastes	RCRA - U Series Wastes
Toluene	108-88-3	None	None	None	U220
ETHYL GLYOXYLATE	924-44-7	None	None	None	None

14. TRANSPORT INFORMATION

DOT	
UN-No:	UN1294
Proper Shipping Name:	Toluene
Hazard Class:	3
Subsidiary Class	No information available
Packing group:	
Emergency Response Guide	130
Number	
Marine Pollutant	No data available
DOT RG (IDS). Special Provisions	
Symbol(s):	No information available
Description:	LIN1294 Toluene 3 II
Decemption	
TDG (Canada)	
UN-No:	UN1294
Proper Shipping Name:	Toluene
Hazard Class:	3
Subsidiary Risk:	No information available
Packing Group:	II No information available
Marine Pollutant	IND Information available
Description.	UN 1294, TOILIENE, 5, 11
ADR	
UN-No:	UN1294
Proper Shipping Name:	Toluene
Hazard Class:	3
Packing Group:	II
Subsidiary Risk:	No information available
Description:	UN1294, Toluene, 3, II
UN-No:	UN1294
Proper Shipping Name:	Toluene
Hazard Class:	3
Subsidiary Risk:	No information available
Packing Group:	II
Marine Pollutant	No information available
EMS:	F-E
Description	UN1294, I Oluene, 3, II
RID	
UN-No:	UN1294

Product code: E1489

Proper Shipping Name:	Toluene
Hazard Class:	3
Subsidiary Risk:	No information available
Packing Group:	II
Description:	UN1294, Toluene, 3, II

ICAO

UN-No:	UN1294
Proper Shipping Name:	Toluene
Hazard Class:	3
Subsidiary Risk:	No information available
Packing Group:	II
Description:	UN1294, Toluene, 3, II

ΙΑΤΑ

UN-No:	UN1294
Proper Shipping Name:	Toluene
Hazard Class:	3
Subsidiary Risk:	No information available
Packing Group:	11
ERG Code:	3L
Special Provisions	No information available
Description:	UN1294, Toluene, 3, II

15. REGULATORY INFORMATION

International Inventories

Components	CAS-No.	U.S. TSCA	KOREA KECL	Philippines (PICCS)	Japan ENCS	CHINA	Australia (AICS)	EINECS-No.
Toluene	108-88-3	Present	Present KE-33936	Present	Present (3)-2	Present	Present	Present 203-625-9
ETHYL GLYOXYLATE	924-44-7	Present	Present KE-27559	Present	Not present	Not present	Not present	Present 213-105-3

U.S. Regulations

 Toluene

 Massachusetts RTK: Present

 New Jersey RTK Hazardous Substance List: 1866

 New Jersey (EHS) List: 1866 500 lb TPQ

 New Jersey - Discharge Prevention - List of Hazardous Substances: Present

 Pennsylvania RTK: Environmental hazard

 Pennsylvania RTK - Environmental Hazard List Present

 Michigan - Critical Materials List: Present

 Minnesota - Hazardous Substance List: Present

 New York Release Reporting - List of Hazardous Substances:

 1000 lb RQ

 1 lb RQ

 Louisana Reportable Quantity List for Pollutants: 1000lbfinal RQ

 454kgfinal RQ

 California Directors List of Hazardous Substances: Present

California Prop. 65: Safe Drinking Water and Toxic Enforcement Act of 1986.

Chemicals Known to the State of California to Cause Cancer:

This product does not contain a chemical requiring a warning under California Prop. 65. (See table below)

Chemicals Known to the State of California to Cause Reproductive Toxicity:

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm (See table below)

Components	CAS-No.	Carcinogen	Developmental Toxicity	Male	Female

				Reproductive Toxicity	Reproductive Toxicity:
Toluene	108-88-3	Not Listed	developmental toxicity	Not Listed	female reproductive toxicity
ETHYL GLYOXYLATE	924-44-7	Not Listed	Not Listed	Not Listed	Not Listed

CERCLA/SARA

Components	CAS-No.	CERCLA - Hazardous Substances and their Reportable Quantities	Section 302 Extremely Hazardous Substances and TPQs	Section 302 Extremely Hazardous Substances and RQs	Section 313 - Chemical Category	Section 313 - Reporting de minimis
Toluene	108-88-3	1000 lb final RQ 454 kg final RQ	None	None	None	1.0 % de minimis concentration
ETHYL GLYOXYLATE	924-44-7	None	None	None	None	None

U.S. TSCA

Components	CAS-No.	TSCA Section 5(a)2 - Chemicals With Significant New Use Rules (SNURS)	TSCA 8(d) -Health and Safety Reporting
Toluene	108-88-3	Not Applicable	10/04/1982 10/04/1992
ETHYL GLYOXYLATE	924-44-7	Not Applicable	Not Applicable

Canada

WHMIS hazard class:

B2 Flammable liquid D2A Very toxic materials D2B Toxic materials

Components

Toluene

WHIMHAZ

B2 D2A D2B

Canada Controlled Products Regulation:

This product has been classified according to the hazard criteria of the CPR (Controlled Products Regulation) and the MSDS contains all of the information required by the CPR.

Components	WHMIS Ingredient Disclosure List -
Toluene	1 %

Inventory

Components	CAS-No.	Canada (DSL)	Canada (NDSL)
Toluene	108-88-3	Present	Not Listed
ETHYL GLYOXYLATE	924-44-7	Not Listed	Present

Components	CAS-No.	CEPA Schedule I - Toxic Substances
Toluene	108-88-3	Not listed
ETHYL GLYOXYLATE	924-44-7	Not listed
Components	CAS-No.	CEPA - 2010 Greenhouse Gases Subject
		to Mandatory Reporting
Toluene	108-88-3	Not listed
ETHYL GLYOXYLATE	924-44-7	Not listed

EU Classification

R-phrase(s)

R11 - Highly flammable.

R38 - Irritating to skin.

- R63 Possible risk of harm to the unborn child.
- R65 Also harmful: may cause lung damage if swallowed

R67 - Vapors may cause drowsiness and diziness.

Product code: E1489

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

S -phrase(s)

S 2 - Keep out of the reach of children.

S46 - If swallowed, seek medical advice immediately and show this container or label.

S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

S36/37 - Wear suitable protective clothing and gloves.

Components	CAS-No.	Classification	Concentration Limits:	Safety Phrases
Toluene	108-88-3	F; R11 Xi; R38 Xn; R48/20-65 Repr.Cat.3; R63 R67	No information	S2 S36/37 S46 S62
ETHYL GLYOXYLATE	924-44-7		No information	

The preparation is classified as dangerous in accordance with Directive 1999/45/EC

Indication of danger:

F - Highly flammable.

- Xn Harmful.
- Xi Irritant.



16. OTHER INFORMATION

Preparation Date: Revision Date: Prepared by: 09/12/2016 Not Applicable Roumann Pangilinan

Disclaimer:

All chemicals may pose unknown hazards and should be used with caution. This Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. The physical properties reported in this SDS are obtained from the literature and do not constitute product specifications. Information contained herein does not constitute a warranty, whether expressed or implied, as to the safety, merchantability or fitness of the goods for a particular purpose. Spectrum Chemicals & Laboratory Products, Inc. assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Spectrum assumes no responsibility for the completeness or accuracy of the information contained herein.

End of Safety Data Sheet