

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

**SECTION 1. IDENTIFICATION**

Product name : Hexane

Number : 000000020212

Product Use Description : Laboratory chemicals

Manufacturer or supplier's details : Honeywell International Inc.  
1953 South Harvey Street  
Muskegon, MI 49442

For more information call : 1-800-368-0050  
+1-231-726-3171(Monday-Friday, 9:00am-5:00pm)

**In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414**  
**: Transportation (CHEMTREC): 1-800-424-9300 or**  
**+1-703-527-3887**  
:  
: (24 hours/day, 7 days/week)

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Form : liquid

Color : colourless

Odor : characteristic

**Classification of the substance or mixture**

Classification of the substance or mixture : Flammable liquids, Category 2  
Skin irritation, Category 2  
Reproductive toxicity, Category 2  
Specific target organ toxicity - single exposure, Category 3,  
Central nervous system  
Specific target organ toxicity - repeated exposure, Category 2,  
Peripheral nervous system, Central nervous system  
Aspiration hazard, Category 1

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

**GHS Label elements, including precautionary statements**

Symbol(s)

:



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
Keep cool.  
Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Formula : C<sub>6</sub>H<sub>14</sub>

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
n-Hexane	110-54-3	>=90.00 - <=100.00 %

**SECTION 4. FIRST AID MEASURES**

General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

Inhalation : Remove to fresh air. Keep patient warm and at rest. If symptoms persist, call a physician.

Skin contact : After contact with skin, wash immediately with plenty of soap and water. Call a physician if irritation develops or persists.

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Eye contact : Rinse thoroughly with plenty of water, also under the eyelids. Protect unharmed eye. Consult a physician.

Ingestion : When swallowed, allow water to be drunk. Do NOT induce vomiting. Call a physician immediately.

**Notes to physician**

Most important symptoms/effects, acute and delayed : No information available.

Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting : Flammable.  
Vapours may form explosive mixtures with air.  
Vapours are heavier than air and may spread along floors.  
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- |   |   |  |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Evacuate personnel to safe areas.<br>Wear personal protective equipment. Unprotected persons must be kept away.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.   |
| Environmental precautions   | : | Do not flush into surface water or sanitary sewer system.  |
| Methods and materials for containment and cleaning up               | : | Ventilate the area.<br>Do not use sparking tools.<br>Use explosion-proof equipment.<br>Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). |

**SECTION 7. HANDLING AND STORAGE****Handling**

- |   |   |  |
|---|---|--|
| Precautions for safe handling                   | : | Exhaust ventilation at the object is necessary.<br>Use explosion-proof equipment.  |
| Advice on protection against fire and explosion | : | Keep product and empty container away from heat and sources of ignition.<br>No smoking.<br>Take precautionary measures against static discharges.<br>Vapours may form explosive mixtures with air. |

**Storage**

- |  |   |  |
|--|---|--|
| Conditions for safe storage, including any incompatibilities | : | Store in area designed for storage of flammable liquids. Protect from physical damage.<br>Keep containers tightly closed in a dry, cool and well-ventilated place.<br>Store in original container. |
|--|---|--|

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.  
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.  
Avoid exposure - obtain special instructions before use.
- Engineering measures : Use with local exhaust ventilation.  
Prevent vapour buildup by providing adequate ventilation during and after use.
- Eye protection : Safety glasses with side-shields
- Hand protection : Wear nitrile rubber gloves to avoid contact with the skin.  
Gloves must be inspected prior to use.  
Replace when worn.
- Skin and body protection : Protective suit
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hygiene measures : Take off all contaminated clothing immediately.  
Remove and wash contaminated clothing before re-use.  
Wash hands before breaks and at the end of workday.  
When using do not eat or drink.

**Exposure Guidelines**

Components	CAS-No.	Value	Control parameters	Update	Basis
n-Hexane	110-54-3	SKIN_DES : Skin designation:	Danger of cutaneous absorption	01 2020	ACGIH:US. ACGIH Threshold Limit Values, as amended
n-Hexane	110-54-3	SKIN_DES : Skin designation:	Danger of cutaneous absorption	01 2020	ACGIH:US. ACGIH Threshold Limit Values, as amended
n-Hexane	110-54-3	TWA : Time weighted average	(50 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended

## SAFETY DATA SHEET

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

n-Hexane	110-54-3	REL : Recomm ended exposure limit (REL):	180 mg/m3 (50 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
n-Hexane	110-54-3	PEL : Permissi ble exposure limit	1,800 mg/m3 (500 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
n-Hexane	110-54-3	TWA : Time weighted average	180 mg/m3 (50 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	: liquid
Color	: colourless
Odor	: characteristic
Odor threshold	: Note: No data available
pH	: Note: Not applicable
Melting point/range	: -95 °C
Boiling point/boiling range	: 66 - 69 °C at 1,013 hPa
Flash point	: -15 °F (-26 °C) Method: closed cup

# SAFETY DATA SHEET



## Hexane

**34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Evaporation rate	: Note: No data available
Flammability	: Not applicable
Lower explosion limit	: 1.2 %(V)
Upper explosion limit	: 7.4 %(V)
Vapor pressure	: 540 hPa at 50 °C(122 °F) 160 hPa at 20 °C(68 °F)
Vapor density	: Note: No data available
Density	: 0.660 - 0.668 g/cm3 at 20 °C
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: log Pow: 4.11
Ignition temperature	: 240 °C
Viscosity, dynamic	: 0.31 mPa.s at 20 °C
Viscosity, kinematic	: < 0.5 mm2/s at 40 °C
Molecular weight	: 86.18 g/mol

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.



**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

**SECTION 11. TOXICOLOGICAL INFORMATION**

Acute oral toxicity	: LD50: 15,840 mg/kg Species: Rat
	: LD50: 5,000 mg/kg Species: Mouse
Acute inhalation toxicity	: LC50: 48000 ppm Exposure time: 4 h Species: Rat
Acute dermal toxicity	: LD50: 3,000 mg/kg Species: Rabbit
Skin irritation	: Species: Rabbit Result: irritating
Sensitisation	: Note: No data available

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Aspiration toxicity : May be fatal if swallowed and enters airways.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity effects**

Toxicity to fish : LC50: 2.5 mg/l  
Exposure time: 96 h  
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates : EC50: 2.1 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)

Toxicity to algae : Note: No data available

Toxicity to bacteria : Note: No data available

**Further information on ecology**

Additional ecological information : Should not be released into the environment.  
May cause long-term adverse effects in the aquatic environment.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

**SECTION 14. TRANSPORT INFORMATION**

DOT UN/ID No. : UN 1208  
Proper shipping name : HEXANES

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Class	3
Packing group	II
Hazard Labels	3

<b>IATA</b>	UN/ID No.	: UN 1208
	Description of the goods	: HEXANES
	Class	: 3
	Packaging group	: II
	Hazard Labels	: 3
	Packing instruction (cargo aircraft)	: 364
	Packing instruction (passenger aircraft)	: 353
	Packing instruction (passenger aircraft)	: Y341

<b>IMDG</b>	UN/ID No.	: UN 1208
	Description of the goods	: HEXANES
	Class	: 3
	Packaging group	: II
	Hazard Labels	: 3
	EmS Number	: F-E, S-D
	Marine pollutant	: yes

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

**SECTION 15. REGULATORY INFORMATION****Inventories**

USA. List of Active Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended : On TSCA Inventory

Australia. Inventory of Industrial Chemicals (AIIC), as amended : On the inventory, or in compliance with the inventory

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Canada. Domestic Substances List (DSL), as amended : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS) : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC) : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI) : On the inventory, or in compliance with the inventory

**National regulatory information**

US. EPA CERCLA Hazardous Substances (40 CFR 302) : The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ):

Reportable quantity: 5000 lbs  
: n-Hexane 110-54-3

**SARA 302 Components** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
: n-Hexane 110-54-3


**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

**Hexane****34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

**CERCLA Reportable Quantity** : 5000 lbs**California Prop. 65** :  **WARNING:** This product can expose you to chemicals, listed below, known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

n-Hexane

110-54-3

**Massachusetts RTK** : n-Hexane 110-54-3**New Jersey RTK** : n-Hexane 110-54-3**Pennsylvania RTK** : n-Hexane 110-54-3**SECTION 16. OTHER INFORMATION**

	<b>HMIS III</b>	<b>NFPA</b>
Health hazard	: 1*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

\* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

**Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

**Hexane**

**34484-2.5L**

Version 1.2

Revision Date 05/10/2024

Print Date 05/11/2024

Previous Issue Date: 06/04/2019

Prepared by Honeywell Energy and Sustainability Solutions Product Stewardship Group Product Stewardship Group