SAFETY DATA SHEET SPECTRUM®



Revision date 23-May-2022 Revision Number 16

1. Identification

Product identifier

Product Name DEHYDRATED ALCOHOL, 200 PROOF, USP, EP, BP

Other means of identification

Product Code(s) E1068

UN/ID no UN1170

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use

No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

Spectrum Chemical Mfg. Corp. 14422 South San Pedro St. Gardena, CA 90248 (310) 516-8000

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. Hazard(s) identification

Classification

Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 2

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Causes serious eye irritation

May damage fertility or the unborn child

May cause respiratory irritation

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Highly flammable liquid and vapor



Appearance Clear Physical state Liquid Odor Alcohol

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/.?/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available.

3. Composition/information on ingredients

Substance

Chemical name	CAS No	Weight-%	Trade secret
Ethyl Alcohol 200 proof	64-17-5	100	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid

contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). water spray. Alcohol resistant foam.

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

risk of ignition. Keep product and empty container away from heat and sources of ignition.

In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon Monoxide, Carbon Dioxide.

Explosion data

Large Fire

Sensitivity to mechanical impact none.

Sensitivity to static discharge yes

Special protective equipment for

fire-fighters

Personal precautions

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other information

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Alcohol 200 proof	No data available	1000 ppm TWA	-
64-17-5		1900 mg/m ³ TWA	

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical stateLiquidAppearanceClearColorColorlessOdorAlcohol

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

no data available None known Melting point / freezing point no data available None known Boiling point / boiling range 78 - 79 °C / 172.4 - 174.2 °F None known 12 - 14 °C / 53.6 - 57.2 °F Flash point None known **Evaporation rate** no data available None known Flammability (solid, gas) no data available None known Flammability Limit in Air None known

Upper flammability or explosive 19 %

limits

Lower flammability or explosive 3.3 %

limits

Vapor pressure5.7 - 5.866None knownVapor density1.59None knownRelative density0.79None knownWater solubilityMiscible in waterNone knownSolubility(ies)Miscible with many organic solventsNone known

Partition coefficient -0.31 None known

Autoignition temperature 363 - 426 °C / 685.4 - 798.8 None known

°F

Decomposition temperatureNone knownKinematic viscosityno data availableNone knownDynamic viscosityNo data availableNone known

Other information

Explosive properties

Oxidizing properties

No information available
No information available
No information available

Molecular weight 46.07 VOC Content (%) 99+ %

Liquid DensityNo information availableBulk densityNo information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl Alcohol 200 proof	= 7060 mg/kg (Rat)	-	124.7 mg/L (Rat)4 h
64-17-5			-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization
Germ cell mutagenicity
Carcinogenicity

No information available.
No information available.
No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethyl Alcohol 200 proof	-	Group 1 - Monograph	-	-
64-17-5		100E [2012] in alcoholic		
		beverages		
		Monograph 96 [2010] in		
		alcoholic beverages		

Legend

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. May damage fertility or the unborn child.

Developmental toxicity May cause harm to the unborn child.

STOT - single exposureSTOT - repeated exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.

Target organ effects liver, respiratory system, Eyes, Skin, central nervous system, blood, Reproductive System.

Aspiration hazard No information available.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Ethyl Alcohol 200 proof	-	LC50: 12.0 - 16.0mL/L	-	LC50: 9268 - 14221mg/L
64-17-5		(96h, Oncorhynchus		(48h, Daphnia magna)
		mykiss) LC50: 13400 -		EC50: =10800mg/L (24h,
		15100mg/L (96h,		Daphnia magna) EC50:
		Pimephales promelas)		=2mg/L (48h, Daphnia
		LC50: >100mg/L (96h,		magna)
		Pimephales promelas)		

Persistence and degradability Bioaccumulation

No information available. Inherently biodegradable.

Component Information

Chemical name	Partition coefficient
Ethyl Alcohol 200 proof	-0.32
64-17-5	

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.

14. Transport information

DOT

UN/ID no UN1170
Proper Shipping Name: Ethanol
Hazard class 3
Packing group: II

Special Provisions24, IB2, T4, TP1Marine PollutantSevere Marine PollutantDescription:UN1170, Ethanol, 3, II

Emergency Response Guide

Number

127

TDG

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard class 3
Packing Group: II

Description: UN1170, Ethanol, 3, II

```
MEX
   UN-No
                                   UN1170
   Proper Shipping Name
                                   Ethanol
   Hazard class
                                   3
   Special Provisions
                                   144
   Packing Group
                                   Ш
   Description
                                   UN1170, Ethanol, 3, II
ICAO (air)
   UN-No:
                                   UN1170
   Proper Shipping Name:
                                   Ethanol
   Hazard class
                                   3
   Packing Group:
                                   Ш
   Special Provisions
                                   A58, A180, A3
   Description:
                                   UN1170, Ethanol, 3, II
IATA
                                   UN1170
   UN number
   Proper Shipping Name:
                                   Ethanol
   Transport hazard class(es)
                                   3
   Packing group
                                   Ш
   Description:
                                   UN1170, Ethanol, 3, II
IMDG
   UN number
                                   UN1170
   Proper shipping name
                                   Ethanol
   Transport hazard class(es)
   Packing group
                                   Ш
   EmS-No
                                   F-E, S-D
                                   144
   Special Provisions
   Marine pollutant
                                   NP1
                                   UN1170, Ethanol, 3, II, (12°C c.c.)
   Description
RID
   UN number
                                   UN1170
   Proper Shipping Name:
                                   Ethanol
   Transport hazard class(es)
                                   3
   Packing group
                                   Ш
   Classification code
                                   F1
                                   144, 601
   Special Provisions
   Description:
                                   UN1170, Ethanol, 3, II
   Labels
ADR
   UN number
                                   1170
   Proper Shipping Name:
                                   Ethanol
   Transport hazard class(es)
   Packing group
                                   Ш
   Classification code
                                   F1
                                   (D/E)
   Tunnel restriction code
   Special Provisions
                                   144, 601
                                   1170, Ethanol, 3, II, (D/E)
   Description:
   Labels
ADN
   UN/ID No
                                   UN1170
   Proper shipping name
                                   Ethanol
   Transport hazard class(es)
                                   3
   Packing Group
                                   Ш
   Classification code
                                   F1
   Special Provisions
                                   144, 601
                                   UN1170, Ethanol, 3, II
   Description
   Hazard label(s)
                                   3
   Limited quantity (LQ)
                                   1 L
   ventilation
                                   VE01
   Equipment Requirements
                                   PP, EX, A
```

15. Regulatory information

International Inventories

TSCA Complies

DSL/NDSL Complies EINECS/ELINCS Complies

ENCS This product complies with ENCS: IECSCThis product complies with China:

KECL Complies PICCS Complies

AICS All the constituents of this material are listed on the Australian Inventory of Chemical

Substances (AICS).

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Ethyl Alcohol 200 proof - 64-17-5	developmental toxicity
	carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethyl Alcohol 200 proof	0844	Present	Present

64-17-5

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA

Health hazards 2 Flammability 3 Instability 0

Physical and chemical properties -

HMIS

Health hazards 2 *
Flammability 3
Physical hazards 0
Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date 23-May-2022

Revision NoteNo information available.

<u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet