



# **Material Safety Data Sheet**

| NFPA | HMIS                          | Personal Protective Equipment |
|------|-------------------------------|-------------------------------|
| 230  | Health Hazard 2 Fire Hazard 3 |                               |
|      | Reactivity                    | See Section 15.               |

| Section 1. Chem            | Section 1. Chemical Product and Company Identification Page Number: 1          |                       |  |
|----------------------------|--|-----------------------|--|
| Common Name/<br>Trade Name | 2,6-Lutidine   | Catalog<br>Number(s). | L1145  |
|                            |  | CAS#                  | 108-48-5                                     |
| Manufacturer               | SPECTRUM CHEMICAL MFG. CORP.   | RTECS                 | OK9700000                                    |
|                            | 14422 S. SAN PEDRO STREET<br>GARDENA, CA 90248                                 | TSCA                  | TSCA 8(b) inventory: No products were found. |
| Commercial Name(s)         | Not available.   | CI#                   | Not available.                               |
| Synonym                    | 2,6-Dimethylpyridine   | DI CASE O             | E EMED CENCY                                 |
| Chemical Name              | Not available.   |                       | F EMERGENCY<br>C (24hr) 800-424-9300         |
| Chemical Family            | Not available.   | CALL (310)            | 516-8000                                     |
| Chemical Formula           | C7H9N  |                       |  |
| Supplier                   | SPECTRUM CHEMICAL MFG. CORP.<br>14422 S. SAN PEDRO STREET<br>GARDENA, CA 90248 |                       |  |

| Section 2.Composition and Information on Ingredients |                                       |                |             |                 |              |             |
|--|---------------------------------------|----------------|-------------|-----------------|--------------|-------------|
|  |                                       |                |             | Exposure Limits |              |             |
| Name   |                                       | CAS#           | TWA (mg/m³) | STEL (mg/m³)    | CEIL (mg/m³) | % by Weight |
| 1) {2,6-}Lutidine                                    |                                       | 108-48-5       |             |                 |              | 100         |
| Toxicological Data on Ingredients                    | <b>2,6-Lutidine</b> :<br>ORAL (LD50): | Acute: 400 mg/ | kg [Rat].   |                 |              |             |

# Section 3. Hazards Identification

**Potential Acute Health Effects** 

Very hazardous in case of skin contact (irritant), of eye contact (irritant). Hazardous in case of ingestion, of inhalation (lung irritant). Slightly hazardous in case of skin contact (sensitizer). Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening,

or, occasionally, blistering.

**Potential Chronic Health Effects** 

**CARCINOGENIC EFFECTS**: Not available. **MUTAGENIC EFFECTS**: Not available. TERATOGENIC EFFECTS: Not available.

**DEVELOPMENTAL TOXICITY**: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

| 2,6-Lutidine | Page Number: 2 |
|--------------|----------------|
|--------------|----------------|

| Section 4. First A       | id Measures  |  |
|--------------------------|--|--|
| Eye Contact              | Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention.  |  |
| Skin Contact             | After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cold water may be used. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing. |  |
| Serious Skin Contact     | Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.  |  |
| Inhalation               | Allow the victim to rest in a well ventilated area. Seek immediate medical attention.  |  |
| Serious Inhalation       | Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.  |  |
| Ingestion                | Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.    |  |
| <b>Serious Ingestion</b> | Not available.   |  |

| Section 5. Fire and E.                              | Section 5. Fire and Explosion Data   |  |  |
|---|--|--|--|
| Flammability of the Product                         | Flammable.   |  |  |
| <b>Auto-Ignition Temperature</b>                    | Not available.   |  |  |
| Flash Points  | CLOSED CUP: 37°C (98.6°F).   |  |  |
| Flammable Limits                                    | Not available.   |  |  |
| <b>Products of Combustion</b>                       | These products are carbon oxides (CO, CO2).  |  |  |
| Fire Hazards in Presence of<br>Various Substances   | Not available.   |  |  |
| Explosion Hazards in Presence of Various Substances | Risks of explosion of the product in presence of mechanical impact: Not available.  Risks of explosion of the product in presence of static discharge: Not available.  |  |  |
| Fire Fighting Media<br>and Instructions             | Flammable liquid, soluble or dispersed in water.  SMALL FIRE: Use DRY chemical powder.  LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion. |  |  |
| Special Remarks on<br>Fire Hazards                  | Not available.   |  |  |
| Special Remarks on Explosion Hazards                | Not available.   |  |  |

| Section 6. Accidental Release Measures |  |  |
|--|--|--|
| Small Spill                            | Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.   |  |
| Large Spill                            | Flammable liquid.  Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. |  |

| 2,6-Lutidine | age Number: 3 |
|--------------|---------------|
|--------------|---------------|

| Section 7. Handling and Storage |   |  |
|---------------------------------|---|--|
| Precautions                     | Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.         |  |
| Storage                         | Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F). |  |

| Section 8. Exposure Controls/Personal Protection |   |  |
|--|---|--|
| <b>Engineering Controls</b>                      | Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.              |  |
| <b>Personal Protection</b>                       | Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.  |  |
| Personal Protection in Case of<br>a Large Spill  | Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. |  |
| <b>Exposure Limits</b>                           | Not available.  |  |

| Section 9. Physical and Chemical Properties |                               |       |                 |
|---|-------------------------------|-------|-----------------|
| Physical state and appearance               | Liquid.                       | Odor  | Characteristic. |
| Molecular Weight                            | 107.15 g/mole                 | Taste | Not available.  |
| pH (1% soln/water)                          | Not available.                | Color | Straw color.    |
| <b>Boiling Point</b>                        | 144°C (291.2°F)               |       |                 |
| <b>Melting Point</b>                        | -7°C (19.4°F)                 |       |                 |
| Critical Temperature                        | Not available.                |       |                 |
| Specific Gravity                            | 0.923 (Water = 1)             |       |                 |
| Vapor Pressure                              | Not available.                |       |                 |
| Vapor Density                               | Not available.                |       |                 |
| Volatility                                  | Not available.                |       |                 |
| Odor Threshold                              | Not available.                |       |                 |
| Water/Oil Dist. Coeff.                      | Not available.                |       |                 |
| Ionicity (in Water)                         | Not available.                |       |                 |
| <b>Dispersion Properties</b>                | See solubility in water.      |       |                 |
| Solubility                                  | Easily soluble in cold water. |       |                 |

| 2,6-Lutidine | Page Number: 4 |
|--------------|----------------|
|              |                |

| Section 10. Stability and Reactivity Data |                                     |  |  |
|---|-------------------------------------|--|--|
| Stability                                 | The product is stable.              |  |  |
| Instability Temperature                   | Not available.                      |  |  |
| <b>Conditions of Instability</b>          | Not available.                      |  |  |
| Incompatibility with various substances   | Not available.                      |  |  |
| Corrosivity                               | Non-corrosive in presence of glass. |  |  |
| Special Remarks on<br>Reactivity          | Not available.                      |  |  |
| Special Remarks on<br>Corrosivity         | Not available.                      |  |  |
| Polymerization                            | No.                                 |  |  |

| Section 11. Toxicological Information               |  |  |  |  |
|---|--|--|--|--|
| <b>Routes of Entry</b>                              | Eye contact. Inhalation. Ingestion.  |  |  |  |
| <b>Toxicity to Animals</b>                          | Acute oral toxicity (LD50): 400 mg/kg [Rat].   |  |  |  |
| <b>Chronic Effects on Humans</b>                    | Not available.   |  |  |  |
| Other Toxic Effects on<br>Humans                    | Very hazardous in case of skin contact (irritant). Hazardous in case of ingestion, of inhalation (lung irritant). Slightly hazardous in case of skin contact (sensitizer). |  |  |  |
| Special Remarks on<br>Toxicity to Animals           | Not available.   |  |  |  |
| Special Remarks on<br>Chronic Effects on Humans     | Not available.   |  |  |  |
| Special Remarks on other<br>Toxic Effects on Humans | Not available.   |  |  |  |

| Section 12. Ecological Information                |   |  |  |
|---|---|--|--|
| Ecotoxicity                                       | Not available.  |  |  |
| BOD5 and COD                                      | Not available.  |  |  |
| Products of Biodegradation                        | Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. |  |  |
| Toxicity of the Products of Biodegradation        | The products of degradation are more toxic.   |  |  |
| Special Remarks on the Products of Biodegradation | Not available.  |  |  |

2,6-Lutidine Page Number: 5

## Section 13. Disposal Considerations

Waste Disposal

| Section 14. Transport Information   |   |  |
|-------------------------------------|---|--|
| DOT Classification                  | CLASS 3: Combustible liquid with a flash point greater than 37.8C (100F). |  |
| Identification                      | : Flammable liquid, Toxic, n.o.s. (Lutidine) : UN1992 PG: III             |  |
| Special Provisions for<br>Transport | Not available.  |  |
| DOT (Pictograms)                    |   |  |

### Section 15. Other Regulatory Information and Pictograms

Federal and State Regulations Connecticut carcinogen reporting list.: 2,6-Lutidine TSCA 8(b) inventory: No products were found.

California
Proposition 65
Warnings

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

**Other Classifications** 

WHMIS (Canada) CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).

CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC).

CLASS D-2B: Material causing other toxic effects (TOXIC).

**DSCL** (**EEC**) R10- Flammable.

R22- Harmful if swallowed.

R37/38- Irritating to respiratory system

and skin.

R41- Risk of serious damage to eyes.

HMIS (U.S.A.)



**National Fire Protection Association (U.S.A.)** 

Health



WHMIS (Canada) (Pictograms)





DSCL (Europe) (Pictograms)



TDG (Canada) (Pictograms)



| 2,6-Lutidine | Page I | lumbe | er: ( | 6 |
|--------------|--------|-------|-------|---|
|--------------|--------|-------|-------|---|

ADR (Europe) (Pictograms)



### **Protective Equipment**



Gloves.



Lab coat.



Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.



Splash goggles.

# Section 16. Other Information MSDS Code L3605 References Not available. Other Special Considerations Validated by Sonia Owen on 8/11/2006. Verified by Sonia Owen. Printed 9/12/2006.

### CALL (310) 516-8000

### **Notice to Reader**

All chemicals may pose unknown hazards and should be used with caution. This Material Safety Data Sheet (MSDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this MSDS. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this MSDS is based on technical data judged to be reliable, Spectrum Quality Products, Inc. assumes no responsibility for the completeness or accuracy of the information contained herein.