

Revision number: 1 Revision date: 07/06/2018

1. IDENTIFICATION

TCI AMERICA SAFETY DATA SHEET

| Product name: Product code: | Isopropyl Alcohol [for Spectrophotometry] I0164 | |
|---|---|---|
| Product use: Restrictions on use: | For laboratory research purposes. Not for drug or household use. | |
| Company: TCI America 9211 N. Harborgate Street Portland, OR 97203 U.S.A. Telephone: +1-800-423-8616 / +1-503-283-1681 Fax: +1-888-520-1075 / +1-503-283-1987 e-mail: sales-US@TCIchemicals.com www.TCIchemicals.com | | Emergency telephone number: Chemical Emergencies: TCI America (8:00am - 5:00pm) PST +1-503-286-7624 Transportation Emergencies: Chemtrec 24-Hour +1-800-424-9300 (U.S.A.) +1-703-527-3887 (International) Responsible department: TCI America Environmental Health Safety and Security +1- 503-286-7624 |
| 2. HAZARD(S) IDENTIFICATION | | |
| OSHA Haz Com: CFR 1910.1200: WHMIS 2015: | Eye Damage/Irritation [Category 2A] Toxic to Reproduction [Category 2] Specific Target Organ Toxicity (Single Exposure) [Ca Specific Target Organ Toxicity (Single Exposure) [Ca Specific Target Organ Toxicity (Repeated Exposure) Flammable Liquids [Category 2] | tegory 3] |
| Signal word: | Danger! | |
| Hazard Statement(s): | Highly flammable liquid and vapor Causes serious eye irritation Suspected of damaging fertility or the unborn child Causes damage to: Kidney Central Nervous System May cause respiratory irritation. May cause damage to organs through prolonged or r | epeated exposure: Liver Spleen Blood Vessels |

Pictogram(s) or Symbol(s):



Precautionary Statement(s): [Prevention]

[Response]

[Storage] [Disposal]

Hazards not otherwise classified: [HNOC] understood. Keep away from heat, sparks, open flames and hot surfaces. – No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist, vapors or spray. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Wash hands and face thoroughly after handling. Wear protective gloves, protective clothing, face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If exposed: Call a poison center or doctor. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Obtain special instructions before use. Do not handle until all safety precautions have been read and

Dispose of contents and container in accordance with local, regional, national regulations (e.g. US: 40 CFR Part 261, EU:91/156/EEC, JP: Waste Disposal and Cleaning Act, etc.).

May be harmful if swallowed and enters airways. May be harmful if in contact with skin. May be harmful if swallowed.

Page 2 of 5

| 3. COMPOSITION/INFORMATION O | N INGREDIENTS |
|---|---|
| Substance/mixture: | Substance |
| Components: | Isopropyl Alcohol [for Spectrophotometry] |
| Percent: | >99.5%(GC) |
| CAS RN: | 67-63-0 |
| Aolecular Weight: | 60.10 |
| Chemical Formula: | |
| Synonyms: | 2-Propanol, IPA, Isopropanol |
| Synonyms. | |
| 4. FIRST-AID MEASURES | |
| Description of first aid measures | |
| Inhalation: | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. |
| Skin contact: | Remove/Take off immediately all contaminated clothing. Gently wash with plenty of soap and water. Call a POISON CENTER or doctor/physician. |
| Eye contact: | Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Call a POISON CENTER or doctor/physician. |
| Ingestion: | Call a POISON CENTER or doctor/physician. Rinse mouth. |
| Symptoms/effects: | |
| Acute: | Redness. |
| Delayed: | May have effects on the respiratory tract. |
| Indication of any immediate medical atte | ention: |
| Not available. Notes to physician: | |
| No data available | |
| 5. FIRE-FIGHTING MEASURES | |
| Suitable extinguishing media: | Dry chemical, foam, water in large amounts, carbon dioxide. |
| Hazardous combustion products: Other specific hazards: | These products include: Carbon oxides Closed containers may explode from heat of a fire. |
| - | |
| Advice for firefighters: | Wear self-contained breathing apparatus if possible. |
| 6. ACCIDENTAL RELEASE MEASU | RES |
| Personal precautions, protective | |
| equipment and emergency procedures: | Use extra personal protective equipment (self-contained breathing apparatus). Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by repine off, etc. |
| | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. |
| Environmental precautions: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. |
| Environmental precautions: Methods and materials for containment | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In |
| Environmental precautions: Methods and materials for containment | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be |
| Environmental precautions: Methods and materials for containment and cleaning up: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: 7. HANDLING AND STORAGE | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment. |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: 7. HANDLING AND STORAGE Precautions for safe handling: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment. Handling is performed in a well ventilated place. Wear suitable protective equipment. Prevent generation of vapour or mist. Keep away from heat/sparks/open flame/hot surfacesNo smoking. Tak measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Wash hands and face thoroughly after handling. Use a closed system if possible. Use a ventilation, local exhaust if vapour or aerosol will be generated Avoid all contact! |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: 7. HANDLING AND STORAGE Precautions for safe handling: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment. Handling is performed in a well ventilated place. Wear suitable protective equipment. Prevent generation of vapour or mist. Keep away from heat/sparks/open flame/hot surfacesNo smoking. Tak measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Wash hands and face thoroughly after handling. Use a closed system if possible. Use a ventilation, local exhaust if vapour or aerosol will be generated Avoid all contact! |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: 7. HANDLING AND STORAGE Precautions for safe handling: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment. Handling is performed in a well ventilated place. Wear suitable protective equipment. Prevent generation of vapour or mist. Keep away from heat/sparks/open flame/hot surfacesNo smoking. Tak measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Wash hands and face thoroughly after handling. Use a closed system if possible. Use a ventilation, local exhaust if vapour or aerosol will be generated Avoid all contact! |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: 7. HANDLING AND STORAGE Precautions for safe handling: | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment. Handling is performed in a well ventilated place. Wear suitable protective equipment. Prevent generation of vapour or mist. Keep away from heat/sparks/open flame/hot surfacesNo smoking. Tak measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Wash hands and face thoroughly after handling. Use a closed system if possible. Use a ventilation, local exhaust if vapour or aerosol will be generated Avoid all contact! y incompatibilities Keep container tightly closed. Store in a cool, dark and well-ventilated place. Store locked up. |
| Environmental precautions: Methods and materials for containment and cleaning up: Prevention of secondary hazards: 7. HANDLING AND STORAGE Precautions for safe handling: Conditions for safe storage, including an | and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc. Prevent product from entering drains. Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment. Handling is performed in a well ventilated place. Wear suitable protective equipment. Prevent generation of vapour or mist. Keep away from heat/sparks/open flame/hot surfacesNo smoking. Tak measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Wash hands and face thoroughly after handling. Use a closed system if possible. Use a ventilation, local exhaust if vapour or aerosol will be generated Avoid all contact! by incompatibilities Keep container tightly closed. Store in a cool, dark and well-ventilated place. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Exposure limits: | |
|-----------------------------------|---|
| ACGIH TLV(TWA): | 200 ppm |
| ACGIH TLV(STEL): | 400 ppm |
| OSHA PEL(TWA): | 400 ppm |
| JSOH OELs(CL): | 400 ppm |
| Appropriate engineering controls: | Follow safe industrial engineering/laboratory practices when handling any chemical. Install a closed system or local exhaust. Also install safety shower and eye bath. |
| Personal protective equipment | |
| Respiratory protection: | Half or full facepiece respirator, self-contained breathing apparatus(SCBA), supplied air respirator, etc. Use respirators approved under appropriate government standards and follow local and national regulations. |
| Hand protection: | Impervious gloves. |
| Eye protection: | Safety goggles. A face-shield, if the situation requires. |
| Skin and body protection: | Impervious protective clothing. Protective boots, if the situation requires. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Physical state (20°C): Form: Colour: Odour: Odor threshold: Odour threshold: | Liquid Clear Colorless Alcoholic No data available No data available | | |
|--|---|--|--|
| Melting point/freezing point: Boiling point/range: Decomposition temperature: Relative density: Kinematic viscosity: | No data available 82°C (180°F) No data available 0.79 2.6mm²/s (25°C) | pH: Vapour pressure: Vapour density: Dynamic Viscosity: | No data available No data available. 2.1 1.35mPa·s (40°C) |
| Log Pow: | No data available | Evaporation rate(Butyl Acetate=1): | No data available |
| Flash point: Flammability(solid, gas): | 15°C (59°F) No data available | Autoignition temperature: Flammability or explosive limits: Lower: Upper: | 456°C (853°F) 2% 12% |
| Solubility(ies): [Water] [Other solvents] Miscible: Soluble: | Miscible Ether, Alcohols, Acetone Benzene | e, Chloroform, Many organic solvents | |

10. STABILITY AND REACTIVITY

Reactivity: Chemical stability: Possibility of hazardous reactions: Conditions to avoid: Incompatible materials: Hazardous decomposition products: No data available Stable under proper conditions. No special reactivity has been reported. Spark, Open flame, Static discharge Oxidizing agents, Acids, Halogens, Aluminium Carbon dioxide, Carbon monoxide

Page 4 of 5

11. TOXICOLOGICAL INFORMATION

RTECS Number: NT8050000

Disposal of container: Other considerations:

| Acute Toxicity: ihl-rat LC50:16000 ppm/8H skn-rbt LD50:12800 mg/kg | orl-rat LD50:5045 mg/kg |
|---|---|
| Skin corrosion/irritation: skn-rbt 500 mg MLD | |
| Serious eye damage/irritation: eye-rbt 10 mg MOD | eye-rbt 100 mg SEV |
| Respiratory or skin sensitization: No data available | |
| Germ cell mutagenicity: cyt-rat-ihl 1030 ug/m³/16W-I | |
| Carcinogenicity: No data available | |
| IARC: Group 3 (Not classifiable carcinogenic to humans). | |
| Reproductive toxicity: ihl-rat TCLo:3500 ppm/7H (1-19D preg) orl-rat TDLo:3500 g/kg (multigeneration | |
| Aspiration hazard: Target organ(s): Causes damage to: Kidney Central May cause respiratory irritation. May cause damage to organs throu 12. ECOLOGICAL INFORMATION | igh prolonged or repeated exposure: Liver Spleen Blood Vessels |
| | |
| Ecotoxicity: Fish: Crustacea: Algae: | 96h LC50:>100 mg/L (Oryzias latipes) 48h EC50:>1000 mg/L (Daphnia magna) 72h EC50:>1000 mg/L (Selenastrum capricornutum) |
| Persistence / degradability: Bioaccumulative potential(BCF): Mobility in soil | 86% (by BOD) , 94% (by TOC) , 100% (by GC) 3 |
| Log Pow: Soil adsorption (Koc): Henry's Law (PaM ³/mol): | 0.05 25 0.82 |
| 13. DISPOSAL CONSIDERATION | S |
| Disposal of product: Disposal of container: | Recycle to process if possible. It is the generator's responsibility to comply with Federal, State and Local rules and regulations. You may be able to dissolve or mix material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber system. This section is intended to provide assistance but does not replace these laws, nor does compliance in accordance with this section ensure regulatory compliance according to the law. US EPA guidelines for Identification and Listing of Hazardous Waste are listed in 40 CFR Parts 261. The product should not be allowed to enter the environment, drains, water ways, or the soil. Dispose of as unused product. Do not re-use empty containers. |
| Other considerations: | Observe all federal, state and local regulations when disposing of the substance. |

Observe all federal, state and local regulations when disposing of the substance.

14. TRANSPORT INFORMATION

| <u>DOT (US)</u> UN number: UN1219 | Proper Shipping Name: Isopropanol | Class or Division: 3 Flammable liquid | Packing Group: II | |
|---|--------------------------------------|---|----------------------|--|
| IATA UN number: UN1219 | Proper Shipping Name: Isopropanol | Class or Division: 3 Flammable liquid | Packing Group: II | |
| IMDG UN UN1219 numb er: | Proper Shipping Name: Isopropanol | Class or Division: 3 Flammable liquid | Packing Group: II | |
| EmS number: | F-E, S-D | | | |

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA 8b.):

This product is ON the EPA Toxic Substances Control Act (TSCA) inventory.

| SARA 313: | Jus substance a | nd Reportable Quantity: Listed | | |
|--------------------|-----------------|-----------------------------------|---------------------|---|
| SARA 313. | | Not Listed | | |
| State Regulations | <u>S</u> | | | |
| State Right-to-Kn | ow | | | |
| Massachuse | tts | Listed | | |
| New Jersey | | Listed | | |
| Pennsylvania | a | Listed | | |
| California Propos | | Not Listed | | |
| Other Informatio | n | | | |
| NFPA Rating: | | | HMIS Classification | : |
| Health: | 2 | | Health: | 2 |
| Flammability: | 3 | | Flammability: | 3 |
| Instability: | 0 | | Physical: | 0 |
| International Inve | entories | | | |
| Canada: DSL | | On DSL | | |
| EC-No: | | 200-661-7 | | |

16. OTHER INFORMATION

Revision date: 07/06/2018

Revision number: 1

TCI chemicals are for research purposes only and are NOT intended for use as drugs, food additives, households, or pesticides. The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its affiliates or subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.