

Scientific Documentation

Isopropyl Rubbing Alcohol, 70 Percent, USP

Not appropriate for regulatory submission.

Please visit www.spectrumchemical.com or contact Tech Services for the most up-to-date information contained in this information package.

Spectrum Chemical Mfg Corp 769 Jersey Avenue New Brunswick, NJ 08901 Phone 732.214.1300





Table of Contents

Product Specification
Certificate of Analysis
Safety Data Sheet (SDS)
Certification of Current Good Manufacturing Practices (cGMP)
Manufacturing Process Flowchart
Technical Statements
Elemental Impurities Statement
Residual Solvents Statement
General Label Information – Sample Label



Specification for Isopropyl Rubbing Alcohol, 70 Percent, USP (IS120)

Item Number	IS120	
Item	Isopropyl Rubbing Alcohol, 70 Percent, USP	
CAS Number		
Molecular Formula	C ₃ H ₈ O	
Molecular Weight		
MDL Number		
Synonyms	2-Propanol 70 Percent ; Isopropanol ; Isopropyl Alcohol ; 2-Propanol	

Test	Specificat	ion
	Min	Max
ASSAY (C ₃ H ₈ O)	68.0	72.0 %
ACIDITY	TO PASS TEST	
SPECIFIC GRAVITY @ 20°C	0.872	0.883
NONVOLATILE RESIDUE		0.01 %
ELEMENTAL IMPURITIES	AS REPORTED	
IDENTIFICATION	TO PASS TEST	
CERTIFIED HALAL		
APPEARANCE		
RETEST DATE		
DATE OF MANUFACTURE		
RESIDUAL SOLVENTS	AS REPORTED	
CLASS 2 (SOLVENT) / METHANOL		
CLASS 3 (solvent) / ACETONE		
CLASS 3 (solvent) / ETHANOL		
CLASS 3 (solvent) / 1-PROPANOL	•	
MONOGRAPH EDITION		

Spectrum Chemical Mfg Corp

Corporate Headquarters: West Coast Facility: 769 Jersey Ave. 14422 S. San Pedro St.

Spectrum Chemical Mfg Corp

Corporate Headquarters:West Coast Facility:New Brunswick, NJ 08901Gardena, CA 90248732.214.1300310.516.8000



Certificate Of Analysis

Item Number	IS120	Lot Number	2ND0054
Item	Isopropyl Rubbing Alcohol, 70 Percent, USP	Molecular Formula	C ₃ H ₈ O

TEST	SPECIFICATION		RESULT	
IEST	MIN	MAX	RESULI	
ASSAY (C ₃ H ₈ O)	68.0	72.0 %	69.2 %	
ACIDITY	TO PASS TEST		PASSES TEST	
SPECIFIC GRAVITY @ 20°C	0.872	0.883	0.880	
NONVOLATILE RESIDUE		0.01 %	<0.01 %	
ELEMENTAL IMPURITIES	AS REPORTED		NO ELEMENTAL IMPURITIES PRESENT	
IDENTIFICATION	TO PASS TEST		PASSES TEST	
CERTIFIED HALAL			CERTIFIED HALAL	
APPEARANCE			COLORLESS LIQUID	
RETEST DATE			07-FEB-2029	
DATE OF MANUFACTURE			09-FEB-2024	
RESIDUAL SOLVENTS	AS REPORTED			
CLASS 2 (SOLVENT) / METHANOL			<3000 ppm	
CLASS 3 (solvent) / ACETONE			<5000 ppm	
CLASS 3 (solvent) / ETHANOL			<5000 ppm	
CLASS 3 (solvent) / 1-PROPANOL			<5000 ppm	
MONOGRAPH EDITION			USP 2023	

Certificate of Analysis Results Entered By:

CACEVEDO Charmian Acevedo 10-APR-24 13:28:48

Spectrum Chemical Mfg Corp 755 Jersey Avenue New Brunswick 08901 NJ



Certificate of Analysis Results Approved By:

AWILLIAMS Allison Williams 10-APR-24 13:40:19 All pharmaceutical ingredients are tested using current edition of applicable pharmacopeia.

Read and understand label and SDS before handling any chemicals. All Spectrum's chemicals are for manufacturing, processing, repacking or research purposes by experienced personnel only. It is the customer's responsibility to provide adequate hazardous material training and ensure that appropriate Personal Protective Equipment (PPE) is used before handling any chemical.

The Elemental Impurities standards implemented by USP and other Pharmaceutical Compendia reflect a growing understanding of the toxicology of trace levels of elemental impurities that can remain in drug substances originating from either raw materials or manufacturing processes. Identifying and quantifying impurities can be critical to predicting the best possible patient outcomes. Elemental Impurities has been a requirement of all products meeting USP/NF, EP and BP monographs since January 1, 2018. More information can be found in USP sections <232> Elemental Impurities – Limits and <233> Elemental Impurities – Procedures. Data for drug substances furnished by Spectrum Chemical Mfg. Corp can be used to ensure that patient daily exposures by oral administration to the selected elements are not exceeded in the formulation of pharmaceutical products.





Revision date 23-April-2020 Revision Number 2

1. Identification

Product identifier

Product Name ISOPROPYL ALCOHOL, 70 PERCENT, USP

Other means of identification

Product Code(s) IS120

UN/ID no UN1219

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

Spectrum Chemical Mfg. Corp. 14422 South San Pedro St. Gardena, CA 90248 (310) 516-8000

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. Hazard(s) identification

Classification

Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure Highly flammable liquid and vapor



Appearance No information available

Physical state Liquid

Odor Pleasant

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/.?/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed. Causes mild skin irritation.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Trade secret
Isopropyl Alcohol	67-63-0	70	*
Water	7732-18-5	30	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid

contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting. Prolonged contact may cause redness and irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable Extinguishing Media
Large Fire
Dry chemical. Carbon dioxide (CO2). water spray. Alcohol resistant foam.
CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire

extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon Monoxide, Carbon Dioxide.

Explosion data

Sensitivity to mechanical impact none.

Sensitivity to static discharge yes.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take

precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl Alcohol	No data available	400 ppm TWA	-
67-63-0		980 mg/m³ TWA	

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available

Color clear; colorless
Odor Pleasant

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

no data available None known Hq Melting point / freezing point < -40 °C / -40 °F None known Boiling point / boiling range 78.3 °C / 172.9 °F None known 18.3 - 24 °C / 64.9 - 75.2 °F Flash point None known **Evaporation rate** 2.8 (1 = Butyl Acetate) None known Flammability (solid, gas) no data available None known Flammability Limit in Air None known

Upper flammability or explosive 12.7%

limits

Lower flammability or explosive 2%

limits

3.066 None known Vapor pressure Vapor density no data available None known Relative density 0.872 - 0.883 None known None known Water solubility Miscible with water Solubility(ies) Miscible with alcohol None known **Partition coefficient** -0.16 None known **Autoignition temperature** 399 °C / 750.2 °F None known

Decomposition temperatureNone knownKinematic viscosityno data availableNone knownDynamic viscosityNo data availableNone known

Other information

Explosive properties

Oxidizing properties

No information available
VOC Content (%)
No information available
Liquid Density
No information available
Bulk density
No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation. Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged

contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2,671.40 mg/kg **ATEmix (dermal)** 5,798.60 mg/kg

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Water 7732-18-5	90 mL/kg(Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation. Classification based on data available for ingredients. **Serious eye damage/eye irritation**Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization
Germ cell mutagenicity
Carcinogenicity

No information available.
No information available.
No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

		· · · · · · · · · · · · · · · · · · ·		
Chemical name	ACGIH	IARC	NTP	OSHA
Isopropyl Alcohol	-	Group 3 - Not classifiable	-	-
67-63-0		- Monograph 71 [1999]		
	Supplement 7 [198			
		Monograph 15 [1977]		

Legend

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure

Target organ effects

May cause damage to organs through prolonged or repeated exposure.

respiratory system, Eyes, Skin.

Aspiration hazard

No information available.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

Ecotoxicity

	Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
ı				microorganisms	
Ī	Isopropyl Alcohol	EC50: >1000mg/L (72h,	LC50: =11130mg/L (96h,	-	EC50: =13299mg/L (48h,
1	67-63-0	Desmodesmus	Pimephales promelas)		Daphnia magna)
1		subspicatus) EC50:	LC50: =9640mg/L (96h,		
1		>1000mg/L (96h,	Pimephales promelas)		
1		Desmodesmus	LC50: >1400000µg/L		
1		subspicatus)	(96h, Lepomis		
1			macrochirus)		

Persistence and degradability Bioaccumulation

No information available. Inherently biodegradable.

Component Information

Chemical name	Partition coefficient
Isopropyl Alcohol	0.05
67-63-0	

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld

containers.

14. Transport information

DOT

UN/ID no UN1219

Proper Shipping Name: Isopropanol solution

Hazard class 3
Packing group:

Special Provisions IB2, T4, TP1

Marine Pollutant Severe Marine Pollutant

Description: UN1219, Isopropanol solution, 3, II

Emergency Response Guide 129

Number

<u>TDG</u> <u>UN-No:</u> UN1219

Proper Shipping Name: Isopropanol solution

Hazard class

Packing Group:

Description: UN1219, Isopropanol solution, 3, II

MEX

UN-No UN1219

Proper Shipping Name Isopropanol solution

Hazard class 3 Packing Group II

Description UN1219, Isopropanol solution, 3, II

ICAO (air)

UN-No: UN1219

Proper Shipping Name: Isopropanol solution

Hazard class 3
Packing Group: II
Special Provisions A180

Description: UN1219, Isopropanol solution, 3, II

IATA

UN number UN1219

Proper Shipping Name: Isopropanol solution

Transport hazard class(es) 3
Packing group | |

Description: UN1219, Isopropanol solution, 3, II

IMDG

UN number UN1219

Proper shipping name Isopropanol solution

Transport hazard class(es)

Packing group

EmS-No

Marine pollutant

3

F-E, S-D

NP1

Description UN1219, Isopropanol solution, 3, II, (18.3°C c.c.)

RID

UN number UN1219

Proper Shipping Name: Isopropanol solution

Transport hazard class(es) 3
Packing group II
Classification code F1
Special Provisions 601

Description: UN1219, Isopropanol solution, 3, II

Labels 3

<u>ADR</u>

UN number 1219

Proper Shipping Name: Isopropanol solution

Transport hazard class(es)

Packing group

Classification code

Tunnel restriction code

Special Provisions

3

II

(D/E)

601

Description: 1219, Isopropanol solution, 3, II, (D/E)

Labels 3

<u>ADN</u>

UN/ID No UN1219

Proper shipping name Isopropanol solution

Transport hazard class(es) 3
Packing Group II
Classification code F1
Special Provisions 601

Description UN1219, Isopropanol solution, 3, II

Hazard label(s) 3 Limited quantity (LQ) 1 L ventilation VE01

15. Regulatory information

International Inventories

TSCA Complies

DSL/NDSL Complies EINECS/ELINCS Complies

ENCS This product complies with ENCS: IECSC This product complies with China:

KECL Complies PICCS Complies

AICS All the constituents of this material are listed on the Australian Inventory of Chemical

Substances (AICS).

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated under applicable state right-to-know regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA

Health hazards 2 Flammability 3

Instability 0

Physical and chemical properties -

HMIS

Health hazards 2 * Flammability 3 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)

Ceiling Maximum limit value

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date 23-April-2020

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

STEL (Short Term Exposure Limit)

End of Safety Data Sheet



Certification of Compliance with current Good Manufacturing Practices

Dear Valued Customer:

Spectrum Chemical Mfg Corp certifies that the following product(s) is produced, processed, packaged and held in compliance with current Good Manufacturing Practices (cGMP) in accordance with the applicable parts of 21 CFR, parts 210 and 211 of the Code of Federal Regulations.

Catalog Number	Product Name
IS120	Isopropyl Rubbing Alcohol, 70 Percent, USP

Spectrum is an FDA registered and inspected Drug Establishment. Our United States Food and Drug Administration (USFDA) Registration numbers are as follows:

Spectrum-Gardena, CA: 2020632 Spectrum-New Brunswick, NJ: 2246824

Thank you for your interest in Spectrum products. If we may be of further assistance, please feel free to contact the Quality Assurance department at 310-516-8000 or via email at qualityassurance@spectrumchemical.com

Sincerely,

Oralia Chavez


Quality Assurance Specialist

Orda Clary



Manufacturing Process Flowchart

Isopropyl Rubbing Alcohol, 70 Percent, USP - IS120



Spectrum Chemical Mfg Corp

Corporate Headquarters: 769 Jersey Ave.

New Brunswick, NJ 08901

732.214.1300

West Coast Facility:

14422 S. San Pedro St. Gardena, CA 90248

310.516.8000



IS120, Isopropyl Rubbing Alcohol, 70 Percent, USP

Source Statement

The above mentioned catalog item is manufactured by chemical synthesis. No animal or plant derived products are used in the manufacturing process.

BSE/TSE Statement

The above mentioned catalog item does not contain nor is manufactured using any animal derived products and is therefore, BSE/TSE free.

Allergen Statement

The above mentioned catalog item does not contain any of the following:

- Milk
- Egg
- Fish
- Shellfish
- Tree Nuts
- Wheat
- Peanuts
- Soy

- Cereals containing Gluten
- Celery
- Mustard
- Sesame Seed
- Corn
- Latex
- Sulfites > 10 ppm

EU Fragrance Allergen Statement

The above mentioned catalog item does not contain any of the 26 EU fragrance allergens listed in Annex III lines 67-92. These substances are not intentionally added to the following chemical and therefore are not expected to be present.

GMO Statement

The above mentioned catalog item is manufactured without the use of genetically modified organisms and is therefore GMO free.

Melamine Statement

The above mentioned catalog does not use or add melamine to the manufacturing process and is considered melamine-free.



Nitrosamine Statement

Based on knowledge of the manufacturing process, nitrosamine impurities are not known or suspected to be present in this material.

Animal Testing Statement

The above mentioned catalog item has not been tested on animals.

Organic Compliance Statement

The above mentioned catalog item has not been produced using GMOs, irradiation, ethylene oxide (EtO) or sewage sludge.

Shelf Life Statement

The above mentioned catalog item is typically assigned a shelf life of 60 months from the date of manufacture. The actual assigned shelf life for any specific lot should be referenced on the Certificate of Analysis.

Other Chemicals Statement

Spectrum does not have any reason to suspect the above mentioned catalog item contains any of the following chemicals. This product does not come into contact with these chemicals during packaging or storage:

- Aflatoxins
- Antibiotics
- Bisphenol A (BPA)
- CMR Substances

- Parabens
- Pesticides
- Phthalates
- Preservatives



RE: Elemental Impurities - Isopropyl Rubbing Alcohol, 70 Percent, USP (Cat# IS120)

To Whom It May Concern:

Thank you for your interest in Spectrum high quality chemicals.

The above mentioned material complies with the USP<232>, <233> Elemental Impurities and the ICH Q3D Elemental Impurities Guideline. No Class 1, Class 2A, Class 2B or Class 3 elemental impurities are likely to be present.

This information is subject to change and is intended for risk assessment only. It is responsibility of the end user to evaluate suitability of any chemical for the intended use as well as to assess compound-specific limits of daily intake of metal impurities. For lot-specific information, please refer to the respective Certificate of Analysis.

If you have any further questions, please contact us by telephone at 1(800)772-8786 Option 2, or by email at TechServices@spectrumchemical.com.

Sincerely,

Technical Services
Spectrum Chemical Mfg. Corp.

This document has been produced electronically and is valid without a signature.

CORPORATE HEADQUARTERS

769 Jersey Avenue New Brunswick, NJ 08901 PHONE 732.214.1300 FAX 732.246.7132 WEST COAST FACILITY

14422 South San Pedro Street
Gardena, California 90248
PHONE 310.516.8000
FAX 310.516.9843



RE: Residual Solvents - Isopropyl Rubbing Alcohol, 70 Percent, USP (Cat# IS120)

To Whom It May Concern:

Thank you for your interest in Spectrum high quality chemicals.

The above mentioned catalog item complies with the requirements of USP <467> Residual Solvents and ICH Q3C Residual Solvents Guideline. The following solvents are likely to be present:

Residual Solvent	Class	Expected Concentration
Methanol	2	< 3000 ppm
Acetone	3	< 5000 ppm
Ethanol	3	< 5000 ppm
1-Propanol	3	< 5000 ppm

No Class 1 or other solvents are used or produced in the manufacturing process of this material.

For lot-specific information, please refer to the respective Certificate of Analysis.

If you have any further questions, please contact us by telephone at 1(800)772-8786 Option 2, or by email at TechServices@spectrumchemical.com.

Sincerely,

Technical Services
Spectrum Chemical Mfg. Corp.

This document has been produced electronically and is valid without a signature.

CORPORATE HEADQUARTERS

769 Jersey Avenue New Brunswick, NJ 08901 PHONE 732.214.1300 FAX 732.246.7132 WEST COAST FACILITY

14422 South San Pedro Street
Gardena, California 90248
PHONE 310.516.8000
FAX 310.516.9843



Label Information

The Spectrum label presents technical and safety information in an easily understood format. Our technical specialists stay abreast of the latest requirements of the Globally Harmonized System for Classification and Labelling of Chemicals (GHS), as well as the Occupational Safety and Health Administration (OSHA), the Food and Drug Administration (FDA) and other government regulatory agencies in order to ensure compliance, accuracy and concise hazard communication.



- Bar Code
- GHS Hazard Pictograms
- Warning, Safety Data and Precautionary Information
- Product Catalog Number
- Item Name, Form, Grade
- Size/Quantity

- Chemical Abstracts Service (CAS) Registry Number
- Caution Information
- DOT Shipping Information
- Toll-Free 24-Hour Chemical Emergency Telephone Number
- Empirical Formula, Formula Weight and Technical Specifications Panel
- Expiration Information
- Lot Number
- Kosher Certified by Kosher Supervision of America (KSA).
- Storage Color Band
- Halal Certified by IFANCA
- bioCertified

This color-coded band indicates the hazard most likely to be posed by that material under storage conditions. The criteria used to assign band colors have been established by the Storage Code working group of the Society for Chemical Hazard Communication (SCHC). It is recommended that like colors be stored together, unless otherwise stated, based on the color codes indicated to the right. However, it is the responsibility of the customer to check with their local fire department for possible conflicts with our recommendations when storing hazardous chemicals.

Spectrum Chemical Mfg Corp

Corporate Headquarters: 769 Jersey Ave.

New Brunswick, NJ 08901

732.214.1300

14422 S. San Pedro St. Gardena, CA 90248

310.516.8000

West Coast Facility:

